

Trane Model R Physical and Electrical Specifications

MODEL	CRHR	260	261*	320	321*	350	351*	380	381*	400	401*	500	501*	600	601*
NET OIL PRESSURE		30	30	30	30	30	30	30	30	30	30	30	30	30	30
CYLINDERS		4	4	6	6	4	4	6	6	4	4	6	6	6	6
BORE		3.44	3.44	3.44	3.44	3.44	3.44	3.44	3.44	3.44	3.44	3.44	3.44	3.44	3.44
STROKE		2.75	2.75	2.3	2.3	2.3	2.3	2.75	2.75	2.75	2.75	2.3	2.3	2.75	2.75
DISPLACEMENT CFM		103.5	103.5	129.9	129.9	86.6	86.6	155.3	155.3	103.5	103.5	129.9	129.9	155.3	155.3
OIL GRADE		150	150	150	150	150	150	150	150	150	150	150	150	150	150
OIL CHARGE PINTS		20	20	27	27	20	20	27	27	20	20	27	27	27	27
NET WEIGHT		815	815	950	950	815	815	977	977	815	815	950	950	977	977
RATED TONS	R-12	26	26	32	32			38	38						
	R-500														
	R-22					35	35			40	40	50	50	60	60
	R-502					X	X			X	X	X	X	X	X
MOTOR SIZE HP						35	35			40	40	50	50	60	60
ELECTRICAL DATA		A/C AIR COOLED - W/C WATER COOLED													
200-3-60	LRA	485	485	582	582	729	729	725	725	910	910	910	910	990	990
	A/C RLA	103	103	125	125	201	201	140	140	258	258	258	258	316	316
	W/C RLA					164	164	128	128	234	234	234	234	280	280
230-3-60	LRA	420	420	506	506	631	631	630	630	792	792	792	792	860	860
	A/C RLA	90	90	109	109	171	171	122	122	226	226	226	226	275	275
	W/C RLA					149	149	95	95	212	212	212	212	252	252
460-3-60	LRA	210	210	253	253	315	315	315	315	396	396	396	396	430	430
	A/C RLA	45	45	55	55	88	88	61	61	113	113	113	113	138	138
	W/C RLA					74	74	55	55	106	106	106	106	126	126

* Low Lift Valves - Required Below 10⁰ F