

MODEL		2DF0300	2DL0400	2DA0500	2DB0500	2DC0500	2DD0500	2DA0600	2DB0600	2DL0750	2DA0750
								NO	NO	NO	NO
NET OIL PRESSURE		20-60	20-60	20-60	20-60	20-60	20-60	20-60	20-60	20-60	20-60
CYLINDERS		2	2	2	2	2	2	2	2	2	2
BORE		2-5/8	2-1/2	2-9/16	2-5/8	2-1/2	2-1/2	2-9/16	2-5/8	2-1/2	2-9/16
STROKE		1-3/8	1-11/16	1-13/16	1-13/16	1-13/64	1-3/8	1-13/16	1-13/16	1-11/16	1-13/16
DISPLACEMENT CFH		907	1008	1133	1190	716	823	1138	1190	1008	1134
OIL GRADE		150	150	150	150	150	150	150	150	150	150
OIL CHARGE OZ.		80	80	80	80	80/110	80/110	80	80	80/110	80/110
NET WEIGHT		301	324	280	301	300	290	323	323	290	300
RATED BTUH @ SST LISTED X 1000	R12 45°F			58.1							
	R12 0°F										
	R134a 45°F	47.7						59.8	62.8		
	R22 -20°F	11.5	13.8			62.7	72.8	15.8	17.7	90.8	103.0
	R404a -20°F	13.5	16.5			30.2	36.6	19.5	21.0	45.7	53.1
	R502- 20°F										
MOTOR SIZE HP		3	4	5	5	5	5	6	6	7-1/2	7-1/2
ELECTRICAL DATA											
208-230 -3- 60	LRA	102.0	161.0	120.0	120.0	120.0	120.0	161.0	161.0	169.0	169.0
	RLA	16.8	26.3	22.3	19.2	22.3	22.3	28.8	28.2	31.6	32.0
	MCC	23.6	33.8	31.2	26.8	31.2	31.2	35.6	35.6	44.2	44.8
460 -3- 60	LRA	52.0	60.0	60.0	60.0	60.0	60.0	60.0	80.0	85.0	85.0
	RLA	8.1	10.2	10.4	10.2	10.4	10.5	10.2	13.3	13.8	14.1
	MCC	10.5	12.2	14.5	14.3	14.6	14.7	13.6	18.0	19.3	19.4
575 -3- 60	LRA	41.0	49.0	49.0	49.0	49.0	49.0	49.0	63.0	67.0	67.0
	RLA	6.7	7.7	7.9	7.6	7.7	7.9	9.1	9.6	13.2	14.3
	MCC	8.4	10.5	11.1	10.6	10.8	11.1	11.8	13.4	18.5	18.5

Conditions: 130° SCT, 0° to 15° SC, Superheat varies, 65° RGT. MDC1 & MDD1 are 1160 RPM, MDC2 & MDD2 are 1750 RPM.