

## Trane Model E & F Open Drive Physical Specifications

MODEL		3E	40	50	60	80	MODEL		F/3F	30	40	50	60	80
OPEN DRIVE R-22						OPEN DRIVE 'F' MODEL								
NET OIL PRESSURE			75	75	75	75	NET OIL PRESSURE			75	75	75	75	75
CYLINDERS			4	5	6	8	CYLINDERS			3	4	5	6	8
BORE			3.66	3.66	3.66	3.66	BORE			2-3/4	2-3/4	2-3/4	2-3/4	2-3/4
STROKE			2-3/4	2-3/4	2-3/4	2-3/4	STROKE			2	2	2	2	2
DISPLACEMENT CFM			117.2	146.5	175.8	234.4	DISPLACEMENT CFM			36.1	48.1	60.2	72.2	96.2
OIL GRADE			300	300	300	300	OIL GRADE			300	300	300	300	300
OIL CHARGE PINTS			29	31	31	33	OIL CHARGE PINTS			13-1/2	18	19	19	20-1/2
NET WEIGHT			784	884	916	1005	NET WEIGHT			415	485	520	525	575
RATED BTUH X 1000							RATED TONS	R-12		10	13	17	19	20-1/2
	R-22		48.5	60.4	72.8	98.8		R-22		15	20	25	30	40
MOTOR SIZE BHP			63.5	78.7	94.8	128	MOTOR SIZE BHP							